1723 W. 4th Street
Tempe Arizona 85281
Phone: 800.638.6104
Fax: 480.966.6723
Email: sales@covid.com

www.covid.com

CVD 5206

S-VIDEO SWITCHER

6 In, 1 Out

Technical Specifications

Input Overview

Signal	S-Video
Connectors	(6) 4-Pin Mini Din Female (1) BNC Female
Video Impedance	75 Ohms Y/C
Video Level	Y: 0.5 Vpp - 1.5 Vpp C: 143 m Vpp - 429 m Vpp

Output Overview

Signals	S-Video
Connector	(1) 4-Pin Mini Din Female
Video Impedance	75 Ohms Y/C
Video Level	Y: 0.5 Vpp - 1.5 Vpp C: 143 m Vpp - 429 m Vpp
Bandwidth	130 MHz
Differential Gain	< 0.1%
Differential Phase	< 0.5 Degrees

Control	RS232 (9-Pin D-Sub Female Connector) Front Panel Keypad RF Remote (Optional)
Displays	Power On Indicator 7-Segment Channel Readout

Physical Specifications

Dimensions	1U High, 1/2 Rack Wide
(inches)	1.75 H x 8.50 W x 6.00 D
(cm)	4.45 H x 21.59 W x 15.24 D
Enclosure	Aluminum, Black, Texture Finish
Weight	1.6 lbs / 0.73 kg
Input Voltage	110 or 120 VAC Wall Mount, 12 VAC, 1A, UL
Power Dissipated	6 Watts

Accessories

CVD 0185	Rack Mount Ears (optional)
CVD 0003	Power Supply (included)

Other Available Options

CVA 5206 - 6 In, 1 Out S-Video with Stereo Audio Switcher