



VM-216HDMI

2X1:16 HDMI DISTRIBUTION AMPLIFIER



SPECIFICATIONS

INPUTS:	2 on HDMI Connectors.
OUTPUTS:	16 on HDMI Connectors.
BANDWIDTH:	Supports up to 1.65Gbps bandwidth per graphic channel.
COMPLIANCE WITH HDMI STANDARD:	Supports HDMI 1.1 and HDCP.
CONTROLS:	EDID, IN 1, IN 2 and, LOCK buttons, RS-232.
INDICATOR LEDS:	OUTPUT STATUS LEDs
POWER SOURCE:	90-240VAC 50/60Hz 31VA
DIMENSIONS:	19 inch (W), 7 inch (D), 1U (H) rack mountable.
WEIGHT:	2.5kg (5.5lbs) approx.
ACCESSORIES:	Power cord.
OPTIONS:	HDMI/HDMI male-to-male cables, Fiber Optic HDMI Cable (C-FOHM/FOHM).

DESCRIPTION

The VM-216HDMI is a distribution amplifier for HDMI signals. It re-clocks and equalizes one of two selectable input signals and distribute it to 16 independent outputs.

- Max Data Rate - 1.65Gbps.
- HDTV Compatible.
- Kramer Re-Klocking™ & Equalization Technology Rebuilds the digital signal to travel longer distances.
- HDCP Compliant.
- Enhanced EDID (Extended Display Identification Data) - The unit can store and recall a default EDID setting in non-volatile memory from the output, allowing convenient and reliable connection to the source.
- Active Output LED Indicators.
- Worldwide Power Supply - 90-240V AC.
- Standard 19" Rack Mount Size - 1U. Rack "ears" included. Add bullet (not as first or last bullet).

