



VS-21HDMI

2X1 HDMI SWITCHER



SPECIFICATIONS

INPUT:	2 HDMI, 1.2Vpp; DDC signal 5Vpp (TTL).
OUTPUTS:	1 HDMI, 1.2Vpp; DDC signal 5Vpp (TTL).
MAX DATA RATE:	1.65 Gbps.
POWER SOURCE:	12VDC, 300 mA.
DIMENSIONS:	12 cm x 7.5 cm x 2.5 cm (4.7" x 2.95" x 0.98") W, D, H.
WEIGHT:	0.3kg (0.66lbs) approx.
ACCESSORIES:	Power supply, mounting bracket.
OPTIONS:	RK-3T 19 inch rack adapter.
COMPLIANCE WITH HDMI STANDARD:	Supports HDMI 1.2 and HDCP.

DESCRIPTION

The VS-21HDMI is a high performance switcher for HDMI signals. It reclocks and equalizes the signal and switches either of 2 inputs to a single HDMI output.

- Max Data Rate - 1.65Gbps.
- HDTV Compatible.
- Kramer Re-Klocking™ & Equalization Technology Rebuilds the digital signal to travel longer distances.
- HDCP Compliant.
- Enhanced EDID (Extended Display Identification Data) - The unit can store and recall a default EDID setting in non-volatile memory from the output allowing convenient and reliable connection to the source.
- Active Input & Output LED Indicators.
- Compact DigiTOOLS® - 3 units can be rack mounted side-by-side in a 1U rack space with the optional RK-3T rack adapter. Additional rack adapters with other configurations are also available.

