



# VS-311HDMI

SWITCHERS, MATRIX  
SWITCHERS &  
CONTROLLERS

## 3X1 HDMI, STEREO & S/PDIF AUDIO STANDBY SWITCHER



### DESCRIPTION

The VS-311HDMI is a high performance switcher for HDMI video, balanced, unbalanced and S/PDIF audio signals. When configured as a standby switcher, it will switch to a selectable secondary input upon loss of the primary input.

- Max Data Rate - Up to 1.65 Gbps.
- HDTV Compatible.
- Kramer Re-Klocking™ & Equalization Technology Rebuilds the digital signal to travel longer distances.
- HDCP Compliant.
- Enhanced EDID (Extended Display Identification Data) - The unit can store and recall a default EDID setting in non-volatile memory from the output allowing convenient and reliable connection to the source.
- Flexible Control Options - Automatic (standby), RS-232, Ethernet or contact closure.
- Input Priority - Selectable via dip switches.
- Desktop Size - Compact size. Two units can be rack mounted side-by-side in a 1U rack space with the optional RK-80N adapter.

### SPECIFICATIONS

INPUTS:	3 HDMI connectors. 3 S/PDIF digital audio on RCA connectors. 3 unbalanced stereo audio +4dBm on 3.5mm mini jacks.
OUTPUT:	1 HDMI connector. 1 S/PDIF digital audio on an RCA connector. 1 unbalanced stereo audio + 4dBm on a 3.5mm mini jack, with 1 balanced stereo audio on a 5-pin detachable terminal block.
DATA RATE:	Up to 1.65Gbps
POWER SOURCE:	12VDC, 270mA
CONTROLS:	Front panel buttons, Infrared remote control transmitter, RS-232, Ethernet.
DIMENSIONS:	21.6cm x 16.1cm x 4.4cm (8.5" x 6.3" x 1.7") W, D, H.
WEIGHT:	1.2kg (2.6lbs) approx.
ACCESSORIES:	Power supply.
OPTIONS:	Rack adapter RK-80N
COMPLIANCE WITH HDMI STANDARD:	Supports HDMI 1.2 and HDCP.