



**VS-4E**

**SWITCHERS, MATRIX  
SWITCHERS &  
CONTROLLERS**

**4X4 COMPOSITE VIDEO & STEREO AUDIO MECHANICAL SWITCHER**



**SPECIFICATIONS**

<b>INPUTS:</b>	4 video, 1Vpp/75Ω on BNC connectors. 4 audio stereo, up to 36Vpp on RCA connectors.
<b>OUTPUTS:</b>	4 composite video (or RGBS), 1Vpp/75Ω on BNC connectors. 4 audio stereo, up to 36Vpp on RCA connectors.
<b>SWITCHING SYSTEM:</b>	Mechanical, "Break-before-make".
<b>CROSSTALK:</b>	-42dB. Chroma, - 60dB. Sync.
<b>BANDWIDTH (-3DB):</b>	475MHz.(video), 100kHz.(audio).
<b>DIMENSIONS:</b>	18.8cm x 7cm x 7cm (7.4" x 2.7" x 2.7") W, D, H.
<b>WEIGHT:</b>	0.65kg. (1.4lbs) approx.
<b>OPTIONS:</b>	19" Rack adapter RK-4S, RK-4E.

**DESCRIPTION**

The VS-4E is a high performance single crosspoint switcher for composite video and unbalanced audio signals. It independently switches any one of four audio or video signals to a single audio or video output.

- High Bandwidth - 475MHz (-3dB).
- Mechanical (Passive) Switching - No power required.
- Separate Audio & Video Switching - One crosspoint (each).
- Desktop Size - Compact size. Two units can be rack mounted side-by-side in a 2U rack space with the optional RK-4E/S adapter.

