

WP-210E**XGA LINE DRIVER**

EUROPEAN MODEL – NOT AVAILABLE FOR SALE IN THE US



XGA Line Driver wall plate with a VGA/UXGA looping input (HD-15) and an amplified and equalized RGBHV output with cable EQ. level, ID bit and termination controls.

DESCRIPTION**SPECIFICATIONS**

INPUTS:	Looping analog red, green, blue signals: 0.7 Vpp/75 Ω, H and V sync, TTL level, on HD15F connectors.
OUTPUTS:	1 RGBHV on 5 BNC connectors
MAX. OUTPUT LEVEL:	2.2Vpp (XGA)
BANDWIDTH (-3DB):	420MHz, Fully Loaded
DIFF. GAIN:	0.01%
DIFF. PHASE:	0.01 Deg.
K-FACTOR:	<0.05%
S/N RATIO:	73dB
CONTROLS:	Cable EQ. control: 0dB to +6.1dB @ 50 MHz; Level control: -0.8dB to +6.2dB ID BIT button; TERM button; Hs (Horizontal) and Vs (Vertical) Sync switches for TTL/Analog mode.
COUPLING:	AC
POWER SOURCE:	12 VDC, 77mA
DIMENSIONS:	Belgium: 8.0cm x 15.1cm x 4.5cm (3.15" x 5.95" x 1.77"), W, H, D; Germany: 8.0cm x 15.1cm x 4.5cm (3.15" x 5.95" x 1.77"), W, H, D; England and Europe: 8.6cm x 14.6cm x 4.5cm (3.39" x 5.75" x 1.77"), W, H, D
WEIGHT:	0.3 kg (0.67 lbs.) approx
ACCESSORIES:	Power supply