



America's Leading Innovator of Cost Effective Prompter Designs

www.teleprompters.com

Specifications	SF-160
Viewable Size	15 inch
Brightness	450 NTS
Signal Input	SVGA, NTSC S-Video
Video Input Impedance	1 VOLTS P-TO-P
Input Voltage	100-240 VAC 12 Volt DC
Resolution	1024 x 768
Power Consumption	30-35 Watts
Input Connector	15-pin D-Type BNC, 4-Pin
Special Features	Scan-Reverse BNC Loop

Introducing our best selling studio teleprompter...SF-160

*15" LCD monitor with multiple inputs with Metal LCD cabinet.

*Oversized 60x40 Trapezoid shaped mirror True Beamsplitter with anti-reflectant Coating is an industry best

*Works well with any camera or tripod / pedestal

*Hood / Mirror is vertically adjustable for centering your camera lens

*Camera prompter mount is horizontally adjustable to help in balancing

*Extra long lasting lens hood is made with Cordura nylon fabric

*All aluminum components with A durable powder coat finish. Extremely tough!

*3 year conditional warranty. It doesn't get better than that!

*Generally in stock & ready to ship.

*250 Dealers worldwide are ready to serve you!

Contact us today with any additional questions you may have.



Phone 920-232-0220 Fax 920-232-1225 sales@teleprompters.com

www.teleprompters.com