

QuickSet has over seven decades of experience in the design, manufacturing and maintenance of support products providing unsurpassed performance, reliability and service. Durability and reliability are our highest engineering priorities. These standards have helped make Quickset a worldwide leader in support systems technology.

When your product depends upon the performance of a tripod or pan & tilt unit the Samson Series has proven reliable in countless critical applications. This is a result of its unmatched quality, durability and torsional stability.

Today, QuickSet is set apart in the world of instrument positioning suppliers by providing reliable and quality support systems, combined with custom tailored solutions to meet the most demanding requirements of every user.



## Specifications

Product Number and Description:	<b>4-73010-7B</b> Tripod with Elevator	<b>4-73500-7B</b> Tripod with Elevator-Short	<b>4-74425-6A</b> Tripod with Foot Plates	<b>4-74500-6</b> Pedestal Mobile
Load Capacity:	40 lbs (18.2 kg)	40 lbs (18.2 kg)	40 lbs (18.2 kg)	40 lbs (18.2 kg)
Maximum Height:	76" (193 cm)	60" (152 cm)	76" (193 cm)	55" (139.7 cm)
Minimum Height:	34" (86.4 cm)	24" (61 cm)	34" (86.4 cm)	37" (94 cm)
Dimensions (Transport Mode):	41" x 8" (104 x 20 cm)	28" x 8" (71 x 20 cm)	41" x 8" (104 x 20 cm)	41.5" x 10" (105 x 25 cm) (Not Assembled)
Maximum Spread (Diameter):	68" (173 cm)	47" (119 cm)	68" (173 cm)	28" (71 cm)
Weight:	10 lb (4.5 kg)	8.5 lb (3.8 kg)	11 lb (5 kg)	23 lb (10.5 kg)
Leg Sections:	2	3	2	N/A
Column Travel:	18" (45 cm)	18" (45 cm)	18" (45 cm)	18" (45 cm)
Column Outside Diameter	1.75" (4.4 cm)	1.75" (4.4 cm)	1.75" (4.4 cm)	1.75" (4.4 cm)
Wheel Size:	N/A	N/A	N/A	4" x 1" (10 x 2.5 cm) Lockable
Foot Plate Ø:	N/A	N/A	4" Ø (10 cm) Self Leveling 5/8" hole for Spiking	N/A
Rubberball-Spike Ø:	1.5" (3.8 cm)	1.5" (3.8 cm)	N/A	N/A

## Microwave Tripods

Product Number and Description:	<b>4-74420-7B</b> Tripod-Microwave	<b>4-74424-9C</b> Tripod-Microwave with Friction Head
Load Capacity:	35 lbs (16 kg)	35 lbs (16 kg)
Maximum Height:	64" (162 cm)	64" (162 cm)
Minimum Height:	40.5" (103 cm)	34" (86.4 cm)
Dimensions Transport Mode:	45" x 9" (114 x 22.5 cm)	45" x 9" (114 x 22.5 cm)
Maximum Spread:	60" (152 cm)	60" (152 cm)
Weight:	15.5 lb (7 kg)	17 lb (7.8 kg)
Leg Sections:	2	2
Column Travel:	N/A	N/A
Column Outside Diameter:	N/A	N/A
Feet Ø:	4" Ø (10 cm) Self Leveling 5/8" Hole for Spiking	4" Ø (10 cm) Self Leveling 5/8" Hole for Spiking
Pan Movement:	360°	360°
Tilt Movement:	40° up, 90° down	45° up, 90° down
Camera Screw:	1/4-20	1/4-20
Camera Plate:	Fixed 4.5" x 4.5" (11.25 x 11.25 cm)	Quick Change 4" x 4" (10 x 10 cm)



4-74420-7B

## Tripod Heads

### Friction and Geared Heads

Product Number and Description:	<b>4-72011-6B</b> Head-Friction	<b>4-72512-3</b> Head-Geared and Side Tilt	<b>4-72612-S3</b> Head-Geared
Load Capacity:	35 Lbs (16 kg)	25 lbs (11.4 kg)	35 lbs (16 kg)
Dimensions (w/o Control Arms):	5.5" x 6.5" x 6.5" (14.1 x 16.6 x 16.6 cm)	8.5" x 6.5" x 6" (21.6 x 16.5 x 15.2 cm)	11.75" x 8.25" x 5.5" (15.2 x 16.5 x 19 cm)
Weight:	2.5 lbs (1.1 kg)	2.5 lbs (1.1 kg)	2 lbs (1 kg)
Control Arms:	2	0	1
Mounting Type:	Sleeve I.D. 1.75" (4.4 cm)	Sleeve I.D. 1.75" (4.4 cm)	Sleeve I.D. 1.75" (4.4 cm)
Pan Movement:	360°	360°	360°
Tilt Movement:	45° up, 90° down	45° up, 90° down	35° up, 90° down
Gear Ratio:	N/A	1:150	1:150
Camera Screw:	1/4-20	1/4-20	1/4-20
Camera Plate (Adjustable):	2.25" x 4.25" (5.6 x 10.6 cm) Fixed	6.25" x 8.5" (16.5 x 21.6 cm) Fixed	2.25" x 4.25" (5.6 x 10.6 cm) Fixed



4-72011-6




4-72512-3

### Fluid Heads

Product Number and Description:	<b>4-52816-2C</b> Head Fluid Hydro
Load Capacity:	50 lbs (22.68 kg)
Dimensions (w/o Control Arms):	6.75" x 6" x 7" (17.1 x 15.2 x 18 cm)
Weight:	16.5 lb (7.5 kg)
Control Arms:	2
Mounting Base:	Sleeve I.D. 1.75" (4.45 cm)
Pan Movement:	360°
Tilt Movement:	80° up 80° down
Camera Screw:	1/4-20 and 3/8-16
Camera Plate	2.25" x 5" (5.7 x 12.7 cm) Quick Change
Optional Camera Plate P/N 6-16004-8:	2.25" x 8" (5.7 x 20.3 cm) Quick Change



4-72612-S3



4-52816-2C

Accessories

Control Arm  
4-20042-4L, 4-20042-4R



Length:	16" (40.4 cm)
Weight:	14 oz (0.3 kg)
Compatible Heads:	4-25090-8C 4-72612-S3

\*Specify Left or Right

Column Adapter  
4-75750-6



Fits:	Samson Column 1.75" (4.4 cm) O.D.
Accepts:	Hercules Ø Post 1.25" (3.1 cm)
Weight:	12 oz (.340 kg)

Hi-Hat  
4-75350-5



Accepts	Sleeve Mount Heads
Post Diameter	1.75" (4.4 cm)
Post Height	1.87" (4.7 cm)
Flange Diameter	5.62" (14.2 cm)
Overall Height	2.87" (7.2 cm)
Through Holes (4x)	0.418" (1 cm)
Bolt Circle	4.7" (11.9 cm)
Weight	1.4 lbs (0.63 kg)

Spike Ball Foot  
6-15004-9, 6-15000-7



Size:	Ball Ø 1.5", Spike 0.5"
Weight:	1 lbs (.45 kg)

Foot pad  
6-15001-5



Size:	4" Ø (10 cm) 5/8" Thru hole for spiking
Weight:	14 oz (0.396 kg)

Pan and Tilt Adapter  
4-75915



Fits:	Samson Column 1.75" (4.4 cm) O.D.
Accepts:	QPT 20 Pan & Tilts
Weight:	12 oz (0.340 kg)

Dolly  
4-56030-6



Load Capacity:	100 lbs (45.35 kg)
Transport Dimensions:	25.5" x 8.5" (65 x 21.2 cm)
Maximum Spread:	38.5" (98 cm)
Weight:	10 lb (4.5 kg)
Wheels:	4" x 1" (10.1 x 2.5 cm) Wheels Lockable

07/2007 00027